



Track by TRU-ROLL™

Seven styles of TRU-ROLL Track provide for every application required for legitimate stages, movie theatres, performing arts centers, and educational auditoriums.

STRAIGHT TRACK

No 1000 Heavy Duty
No 1200 Medium Duty



No. 1000 and No. 1200 straight tracks are available in motorized, cord operated, or walk-along formats. These tracks have an exclusive drop flange construction coupled with a fin guided carrier design to insure quiet, non-fouling and automatically aligning operation. Both tracks may be rigged as bi-parting, lap, or one-way draw.

TRUSS TRACK

No 2000 Heavy Duty
No 2200 Medium Duty



No. 2000 and No. 2200 tracks are available in straight, curved, or serpentine sections. Both tracks can be supplied for motorized operation. Originally developed to satisfy the requirements of "Cinerama" in the 1950's, these tracks are renowned for providing years of trouble free operation. The parallel strong-back truss construction and aluminum intermediate supports result in an exceptionally strong and durable assembly. Radii can be as small as 18 " (508mm) on the curved sections of these tracks.

CYCLORAMA TRACK**No 2300 Medium Duty****No 2500 Heavy Duty**

No. 2300 and No. 2500 Cyclorama tracks have been a proven choice in auditoriums, television and movie studio applications since 1960. Designed for walk along operation, they can be supplied in straight, curved, or serpentine sections. No. 2500 is available in single, double and triple-track construction, while the No. 2300 can be fabricated in single or double track configurations. A variety of track switching mechanisms are available to suit specific needs. No. 2300 and No. 2500 may be rolled to radii as small as 18" (305mm) and 24" (610mm) respectively. Heavy wall tubing can be substituted on either track for applications requiring extra wide supports or heavy loads. The open rail construction makes for simple maintenance and easy carrier replacement.

LIFT CURTAIN RIGGING**No 2900 Lift Curtain Rigging**

No. 2900 lift curtain rigging is designed for brail, contour and Austrian puff curtains. The system incorporates independent lifting cables to uniformly raise or "sculpt" a drapery to a desired position. Support system may be rigged with a hand winch, locking gear box with removable drill motor, or fully-motorized operation.

All Tracks

Operating pulleys for all rigged systems consist of mold-formed Nylon 6/6 wheels, integrally molded to a ball-bearing hub and mounted on a steel axle. Track carriers for heavy duty systems can be supplied with neoprene tired wheels (for loads up to 25 lbs./carrier) or with ball-bearing nylon-tired wheels (for loads up to 50 lbs./carrier). Both styles incorporate a fin-guided molded nylon body with rubber bumper. Carriers for No. 1000 track may be standard or rear fold (back packing). Carriers for medium duty tracks are fabricated using nylon wheels and feature a one-piece nylon body with integral nylon bumper. Master carriers for all tracks are 4-wheel truck construction, joined by a metal body unit.