

2900 LIFT CURTAIN RIGGING

No. 2900 Lift Curtain Rigging is designed for brail, contour and Austrian puff curtains. The system incorporates independent lifting cables to uniformly raise or "sculpt" a drapery to a desired position. Support system may be rigged with a hand winch or fully-motorized operation. The modular system employs a universal aluminum casting supporting a variety of load pulley and idler combinations. These modular castings may be mounted on 2" O.D. steel tube or 1-1/2" I.D. pipe. A set screw is provided to prevent rotation. Lift cables feeding from these pulleys are typically routed to mule blocks where the load is transferred by clew to a single operating line.



No. 2900 Lift Curtain Hardware include the No. 29 series Lift Curtain Pully & Idler Assemblies, sash weights, wire guide clews and custom mule block and lifting mechanics. Horizontal sliding arbors may be substituted for wire guide clews. Pulleys are 2-1/2" diameter, available with 1/4" or 3/32" cable groove.

Stock Parts List:

- 29 Lift Curtain Pully
- 29-1 Lift Curtain Pully + 1 Idler
- 29-2 Lift Curtain Pully + 2 Idlers
- 29-3 Lift Curtain Pully + 3 Idlers
- 29-4 Lift Curtain Pully + 4 Idlers
- 29-5 Lift Curtain Pully + 5 Idlers
- 29-6 Lift Curtain Pully + 6 Idlers
- 29-8 Lift Curtain Pully + 8 Idlers
- 29-10 Lift Curtain Pully + 10 Idlers
- 29-12 Lift Curtain Pully + 12 Idlers
- 29S Swivel type single line pulley
- WS10 Wood Spacer 4"
- WS11 Wood Spacer 6"
- 79-4 4:1 Line Wire Guide Clew
- 79-6 6:1 Line Wire Guide Clew
- 79-8 8:1 Line Wire Guide Clew
- 79-12 12:1 Line Wire Guide Clew
- 5010-1 1 Pound Sash Weight
- 5010-2 2 Pound Sash Weight



WS-11 WOOD SPACER



79-6 6:1 WIRE GUIDE CLEW

Refer to the No. 2900 Price List for additional detail and pricing.