








# TRU-ROLL CURTAIN TRACK SELECTION GUIDE

Model No.	Cross Section	Working Load, lbs. per Carrier *	Carrier Stacking Length, inches **	Hanger Support Spacing, feet ***	Approximate Shipping Wt. - lb/ft	Description - Application
1000	 2.25" W x 3.25" H	50	2-1/8" ea. (Standard) 2" ea. (Rear-Fold) (+ 8-1/4" Leader)	6	2.7	<b>Heavy Duty Straight Steel Track</b> - Straight tracks are available in motorized, cord operated, or walk-along formats. These tracks have an exclusive drop flange construction coupled with a fin guided carrier design to insure quiet, non-fouling and automatically aligning operation. Tracks may be rigged as bi-parting, lap, or one-way draw with standard or rear-fold carriers.
1200	 1.63" W x 2.25" H	25	1-3/8" ea. (+ 5-7/8" Leader)	4	0.71	<b>Medium Duty Straight Aluminum Track</b> - Straight tracks are available in motorized, cord operated, or walk-along formats. These tracks have an exclusive drop flange construction coupled with a fin guided carrier design to insure quiet, non-fouling and automatically aligning operation. Tracks may be rigged as bi-parting, lap, or one-way draw with standard carriers.
2000	 9" W x 7.375" H	50	2-1/8" ea. (+ 8-1/8" Leader)	5	4.1	<b>Heavy Duty Truss Track</b> - Available in straight, curved, or serpentine sections. Track can be supplied for motorized operation. The parallel strong-back truss construction and aluminum intermediate supports result in an exceptionally strong and durable assembly. Radii on curved sections can be as small as 30" (762mm).
2200	 5.125" W x 4.375" H	25	1-3/8" ea. (+ 3-1/2" Leader)	4	1.28	<b>Medium Duty Truss Track</b> - Available in straight, curved, or serpentine sections. Track can be supplied for motorized operation. The parallel strong-back truss construction and aluminum intermediate supports result in an exceptionally strong and durable assembly. Radii on curved sections can be as small as 18" (508mm).
2300	 2.375" W x 5.125" H	25	1-3/8" ea. (+ 3-7/8" Leader)	4	1.19	<b>Medium Duty Cyclorama Track</b> - Designed for walk along operation, track can be supplied in straight, curved, or serpentine sections. Can be fabricated in single or double track configurations. A variety of track switching mechanisms are available to suit specific needs. May be rolled to radii as small as 18" (305mm). The open rail construction makes for simple maintenance and easy carrier replacement.
2500	 3.25" W x 8.5" H	50	2-1/8" ea. (+ 6-1/8" Leader)	5	1.8	<b>Heavy Duty Cyclorama Track</b> - Designed for walk along operation, track can be supplied in straight, curved, or serpentine sections. Available in single, double and triple-track construction. A variety of track switching mechanisms are available to suit specific needs. May be rolled to radii as small as 24" (610mm). Heavy wall tubing can be substituted for applications requiring extra wide supports or heavy loads.
2900	 6.375" W x 6.25" H	NA	NA	4-5 (Tube) 5-7 (Pipe)	Weight Subject to System Design	<b>Lift Curtain Rigging</b> - Designed for brail, contour and Austrian puff curtains. The system incorporates independent lifting cables to uniformly raise or "sculpt" a drapery to a desired position. Support system may be rigged with a hand winch, locking gear box with removable drill motor, or fully-motorized operation.

\* Working load (drapery weight) per carrier based on 12" standard spacing of carriers for cord operated track. Ball bearing carriers, available for Heavy Duty tracks, are recommended for loads in excess of 50% of maximum working load.

\*\* Multiply the carrier stacking length by the number of carriers and add the sum to the Standard Leader length to obtain the total stacked length.

\*\*\* Recommended distance between track hangers and connection to a rigid support.

Operating pulleys for all rigged systems consist of mold-formed Nylon 6/6 wheels, integrally molded to a ball-bearing hub and mounted on a steel axle. Visit [www.truroll.com](http://www.truroll.com) for a detailed description and specifications of all curtain track components.